

Plenum Electronic Cable, Shielded NEC® 725, Type CMP and/or CL2P UL Classified as to fire and smoke only

Specifications

Conductors	Solid bare copper or stranded bare copper
Insulation	Low smoke-producing, low flame-spread compounds
Shield	Overall Mylar/aluminum foil tape with a stranded, tinned copper drain wire
Jacket	Low smoke-producing, low flame-spread approved compounds

Applications

Security, audio, intercom, power limited control circuits; for installation through air plenums without metal conduit.



Part No.	No. of Cond.	AWG	Cond. Description	Nominal O.D. (in)	Weight (lbs/M-ft)
1P22B70SP	1 pair	22	stranded bare	.110	18
4C22B70SP	4	22	stranded bare	.125	22
6C22B70SP	6	22	stranded bare	.182	28
8C22B70SP	8	22	stranded bare	.199	36
10C22B70SP	10	22	stranded bare	.224	42
12C22B70SP	12	22	stranded bare	.236	50
1P18B10SP	1 pair	18	solid bare	.110	18
1P18B70SP	1 pair	18	stranded bare	.150	26
3C18B70SP	3	18	stranded bare	.160	34
4C18B70SP	4	18	stranded bare	.180	40
6C18B70SP	6	18	stranded bare	.220	50
8C18B70SP	8	18	stranded bare	.240	70
1P16B70SP	1 pair	16	stranded bare	.180	30
4C16B190SP	4	16	stranded bare	.215	50
2C14B190SP	2	14	stranded bare	.225	46
4C14B190SP	4	14	stranded bare	.270	76
Each Pair Shielded:					
2P18T7EPSP	2 pair	18	stranded tinned	.192	48

Other sizes available upon request.

See referenced pages in the Hardware & Supplies section:

Installation Hardware

- Acme 25A or 75A Staple Gun - I-3

Suggested Prep Tool

- 721 Multi-Wire Stripper/Cutter - I-9