

Twisted Pair Plenum

Each Pair Individually Shielded

NEC® 725 Type CMP

Specifications

Conductors	Stranded, tinned copper
Insulation	Low smoke-producing, low flame-spread compounds with cross-reference
Shield	Mylar/aluminum foil tape shields on each pair with common 24 AWG stranded tinned copper drain wire
Configuration	Twisted pairs, color-coded
Jacket	Low smoke-producing, low flame-spread approved compounds



Applications

Special audio, communications and instrumentation uses requiring shielded groups to isolate circuits.

Part No.	No. Pair	Nominal O.D. (in)	Weight (lbs/M-ft)	Color Code
2P22T7EPSP	2	.174	33	Pair 1: Red/Black Pair 2: Black/White
3P22T7EPSP	3	.241	52	Pair 1: Red/Black Pair 2: Black/White Pair 3: Black/Green
6P22T7EPSP	6	.346	90	Pair 1: Red/Black Pair 2: Black/White Pair 3: Black/Green Pair 4: Black/Blue Pair 5: Black/Yellow Pair 6: Black/Brown

See referenced pages in the Hardware & Supplies section:

Installation Hardware

- Acme 25AC Staple Gun - I-3

Suggested Prep Tool

- 721 Multi-Wire Stripper/Cutter - I-9