



PREFORMED LINE PRODUCTS
The connection you can count on.

For All-Dielectric
Self Supporting (ADSS) Cables
FIBERLIGN® CLAS STORAGE



- COMMUNICATIONS
- ENERGY
- SPECIAL INDUSTRIES
- SOLAR

Fiberlign®





COYOTE Dome Bracket Kit



18" Cable Loop



20" Cable Loop



World Headquarters
660 Beta Drive
Cleveland, Ohio 44143

Mailing Address:
P.O. Box 91129
Cleveland, Ohio 44101

Telephone: 440.461.5200
Fax: 440.442.8816
Web Site: www.preformed.com
E-mail: inquiries@preformed.com

© 2008 Preformed Line Products
Printed in U.S.A.
CO-SS-1037-1
08.08.3M

PLP Fiber Optic Products

FIBERLIGN® CLAS Storage - PATENT PENDING

Center-Lock Aerial Slack Storage System for All-Dielectric Self Supporting (ADSS) Cables

The FIBERLIGN Center-Lock Aerial Slack (CLAS) Storage System provides In-Span storage for ADSS cables up to 1" (25mm) in diameter. It is designed to maximize ease of installation, accept a wide range of cable sizes, and allow for cable only or butt splice applications.

Features

- Centerlock hinge design
- Heavy duty UV resistant strap fasteners - no metal fasteners
- Dual purpose apertures
- Expansion tabs
- Abrasion protector or Uni-Group Cable Guide (UCG)

Benefits

- Swing open at center lock-hinge and rest on top of main cable for convenient positioning and simple attachment.
- Long hinge design distributes load along cable interface
- Folds and separates at the hinge for efficient storage
- Minimized labor and installation time - straps cinch quickly and secure to the main cable eliminating the need for tools and metal fasteners.
- Safe with all dielectric materials with superior system life
- Straps secure cable and lock cable storage bracket through common aperture
- Expansion tabs allow 20" (508 mm) maximum loop diameter storage
- Abrasion protectors - economical protection for cable passing the pole
- UCG - guides cable past the pole through Low Profile applications between communication and utility zones
- UCG - Designed for banded (metal pole) or lagged (wood pole) applications - no extra brackets required

Installation Options

- For smaller cables, with diameters of 0.5" (12.7mm) or less, elastomer tubing is provided to build surface contact when securing the CLAS Bracket.
- 18" (457mm) cable loop diameters are stored against the cable channel.
- For butt splice applications, the expansion tabs provide support for an outer cable loop wrap, or for large cables, and over and under cable loop configuration.

Order Catalog # and choose options
710012375

Closure Bracket Kit
(M,C,R,R1,S,D1,blank)

Pole Pass Type
(A,U)

Extra Cable Ties
(T1,blank)

Aerial Closure Bracket Kits	Option
No Brackets – Cable Storage Only	Blank
Universal Messenger Adaptor Bracket – All Closures	M
Classic COYOTE PUP, 6"x22", and 8.5"x22"	C
Classic COYOTE RUNT	R
COYOTE In-Line RUNT Closure	R1
Stainless Steel Splice Case	S
6.5" COYOTE Dome Option	D1
Pole Pass Type	Option
Abrasion Protectors	A
Uni-Group Cable Guide	U
Extra Cable Ties	Option
No Extra Ties (10 included in kit)	Blank
25 Extra Heavy Duty Cable Ties	T1



Abrasion Protectors